





RoHS Compliant



Rev.	change details	effective date	updated by	date
A	Initial release	2020.12.19	FHY	20.12.19





Straight socket connector low profile height 2.8mm: solder tail, double row, low profile. Availability from: 2 to 40 contacts. Standard number of contacts 40.



Straight socket connector low profile height 2.8mm: solder tail, double row, low profile. Availability from: 2 to 80 contacts. Standard number of contacts 80.



Straight socket connector height 4.2mm: solder tail. Availability from: 2 to 40 contacts. Standard number of contacts 40.



Straight socket connector height 4.2mm: solder tail. Availability from: 4 to 80 contacts. Standard number of contacts 80.

Std. Material
 Insulator : Black glass filled polyester PPS-GF30-FR
 Flammability : UL94V-0
 Sleeve : Brass CuZn 36Pb3(36000)
 Contact cilp (6 finger) : Beryllium copper (C17200)
 Mating pin ϕ : 0.40 to 0.66 mm or 0.50SQ
 Forces : (polished steel gauge ϕ 0.46mm)
 -Insertion : 0.7 N typ.
 -Withdrawal : 0.4N typ.
 Mechanical life : min 500 cycles
 Rated current : 3Amp
 Contact resistance: Max 10m Ω
 Dielectric resistance : Min 1000V_{RMS}

Temperature
 Operating Temp. : -40 $^{\circ}$ C to 105 $^{\circ}$ C
 Max. Processing Temp.: 260 $^{\circ}$ C for 10s
Packing : PE bag or agree on _____

Ordering Information

No. of Pins	Contact Plating	Insulator Material
Rows*Pins 1/2 x 40	SN: Tin <input type="checkbox"/> G0: 0.8u" Gold <input type="checkbox"/> G1: 1u" Gold <input type="checkbox"/> G2: 1.5u" Gold <input type="checkbox"/> G3: 2u" Gold <input type="checkbox"/> G4: 3u" Gold <input type="checkbox"/> G5: ___u" Gold <input type="checkbox"/>	A: PBT <input type="checkbox"/> B: PA6T <input type="checkbox"/> C: PA9T <input type="checkbox"/> D: PA66 <input type="checkbox"/> E: PA46 <input type="checkbox"/> F: LCP <input type="checkbox"/> G: _____ <input type="checkbox"/>
Ordering:(N) 1/2 x <input type="text"/>		

Ordering Dimensions

A	B	C	D	H	W
PA	PB	PC	PD	PW	L

Remarks:

UNLESS OTHERWISE STATED DIMENSIONS IN mm TOLERANCE:	ORIGINAL BY	
	DRAWN: FHY	
	CHECKED: FY	
	APPROVED: FY	
DATE: 2020.12.19		
ANGLEAR $\pm 1^{\circ}$	LINEAR X 0.5 X.X ± 0.2 X.XX ± 0.1	

深圳市征华电子有限公司
 Shenzhen ZWON Electronics Co.,Ltd.
 SERIES: Round FH2.0*2.8/Straight
 TYPICAL MODEL: 2.0圆孔排母 塑高2.8 180度

Drawing No.	DRXXX-XX	
Scale	Revision	Sheet
FIT	A	1 of 1
ZWON P/N:		
Customer P/N:		