






RoHS Compliant



Rev.	change details	effective date	updated by	date
A	Initial release	2020.12.19	FHY	20.12.19



Recommended P.C.B. Layout



(10.00) Terminal Height



Std. Material

Contact: Brass  
 Contact Plating: 1u" Au over 30u" Ni Min.  
 Insulator: PBT(UL94V-0).  
 Insulator Colour: Black

Temperature

Operating Temp.: -40°C to 105°C  
 Max. Processing Temp.: 140°C

Electronic Specifications

Current Rating : 1 AMP  
 Contact Resistance : 20mΩ Max.  
 Insulation Resistance : 1000MΩ Min.  
 Withstanding Voltage : AC 1000V for 60s

Packing : Tray or agree on \_\_\_\_\_

Ordering Information

No. of Pins	Contact Plating	Insulator Material
Rows*Pins 2 x 50	SN: Tin <input type="checkbox"/> G0: 0.8u" Gold <input type="checkbox"/> G1: 1u" Gold <input type="checkbox"/> G2: 1.5u" Gold <input type="checkbox"/> G3: 2u" Gold <input type="checkbox"/> G4: 3u" Gold <input type="checkbox"/> G5: __u" Gold <input type="checkbox"/>	A: PBT <input type="checkbox"/> B: PA6T <input type="checkbox"/> C: PA9T <input type="checkbox"/> D: PA66 <input type="checkbox"/> E: PA46 <input type="checkbox"/> F: LCP <input type="checkbox"/> G: _____ <input type="checkbox"/>
Ordering:(N) 2 X <input type="checkbox"/>		

Ordering Dimensions

A	B	C	D	H	W
PA	PB	PC	PD	PW	L

Remarks:

UNLESS OTHERWISE STATED		ORIGINALLY BY
DIMENSIONS IN mm		DRAWN: FHY
TOLERANCE:		CHECKED: FY
ANGLEAR ±1°	LINEAR X 0.5	APPROVED: FY
	X.X ±0.2	DATE:2020.12.19
	X.XX ±0.1	



深圳市征华电子有限公司  
 Shenzhen ZWON Electronics Co.,Ltd.



SERIES: IDC1.27\*2.54\*5.2/Three-piece  
 TYPICAL 1.27x2.54 IDC 塑高5.2 Y型  
 MODEL: 三件式 带凸点

Drawing No.	DRXXX-XX	
Scale	Revision	Sheet
FIT	A	1 of 1
ZWON P/N:		
Customer P/N:		